



THE SPECIAL APPLICATION NEEDLE MR

– DEVELOPED FOR AUTOMATED SEWING PROCESSES
WITH MULTIDIRECTIONAL FEEDING SYSTEMS



In the clothing industry, the shoe industry, and in the processing of technical textiles, an increasing number of computerized sewing machines are in operation. The same requirements apply to all these fields of application:

- **High productivity coupled with maximum process reliability.**
- **Flawless, perfect seams with maximum load-bearing capacity.**


These requirements place stringent demands on sewing machine needles working in automated sewing processes. Standard sewing needles are frequently unable to meet this need, resulting in problems during sewing such as needle breakage, untidy seams (skipped stitches, thread breakage) and material damage.

The answer to all these problems is the Groz-Beckert MR needle.


THE MR NEEDLE AND ITS SPECIAL FEATURES

Stability

With its special blade and scarf geometry, the Groz-Beckert MR needle offers outstanding bending resistance (deflection resistance), lending it extreme stability over its entire working area.



BLADE CROSS-SECTION




SCARF CROSS-SECTION

Added to this is an unusually deep and extended scarf. This permits extremely tight adjustment of the looper to the needle. The deep thread groove, extending also into the eye area, guarantees optimum protection of the thread.


Benefits:

- Less needle deflection
- Less needle breakage
- Fewer skipped stitches
- Less thread breakage



Multidirectional sewing

Computerized sewing machines are capable of producing seams with frequent changes of sewing direction at a constant sewing speed. This type of operation is known as multidirectional sewing.



Cross-section at centre eye


When penetrating the material, a needle reaches its maximum penetration force in this needle area. This increases to a disproportionately high degree as needles with a higher displacement cross-section are used. The MR needle has been designed to ensure that its penetration force remains significantly below that of a standard needle.



STANDARD



MR NEEDLE



Thread loading





When changing the sewing direction, the sewing thread is pulled out of the needle eye in different directions. During its downward stroke, the needle slides along the tensioned sewing thread. This can result in changes in the thread twist, and consequently to instable loop formation.

Loop formation

The needle's special asymmetrically shaped thread sliding area inside the eye of the Groz-Beckert MR needle guarantees stable loop formation even under unfavourable sewing conditions, eliminating the possibility of negative loop formation (*) and thread twist.

The benefit:

- Fewer skipped stitches



Thread pickup

Difficult sewing operations can result in the thread unwinding during loop formation. Single yarns or filaments can be picked up and torn off by the looper point. The risk of unwinding is reduced by the special thread guidance system used in the Groz-Beckert MR needle. Its extreme scarf depth permits very tight looper adjustment, resulting in optimum security during loop pick-up.

The benefits:

- Less thread splicing
- Less thread breakage

THE BENEFITS OF THE MR NEEDLE

- Less needle breakage
- Optimum security against skipped stitches
- Optimum protection of the sewing fabric
- Less needle breakage
- Less thread splicing
- Extremely tight adjustment of looper to needle possible
- High productivity due to reduced machine downtime
- Reduced production costs

THE PRODUCT RANGE

GB designation	Point	SNF Cat. No.	SNF Point	Thickness range									
				2.0	2.5	3.0	3.5	4.0	4.5	5.0	6.0	7.0	
				65-70	75-80	85-90	95-100	105-110	120	125-130	140-160	180-200	
DBx1 MR	R	1515-01-	SET	●	●	●	●	●			●		
DBx1 MR FFG	FFG	1515-06-	L Ball	●	●	●	●	●					
62x45 MR	R	4107-01-	SET								●	●	
62x57 MR	R	3260-01-	SET					●	●	●			
UY128GAS MR	R	3651-01-	SET		●	●	●	●	●	●	●	●	
UY128GAS MR FG	FG	3651-07-	M Ball					●	●	●			
134 K MR	R	1910-01-	SET					●		●			
134 MR	R	1955-01-	SET	●	●	●	●	●	●	●	●	●	
134 MR FFG	FFG	1955-06-	L Ball	●	●	●	●	●	●	●	●	●	
134 MR FFG GEBEDUR®	FFG	-	L Ball	●	●	●	●	●	●	●	●	●	
134 MR FG	FG	1955-07-	M Ball					●	●	●	●	●	
134-35 MR	R	7225-01-	SET			●		●	●	●	●	●	
135X17 MR	R	3355-01-	SET		●	●	●	●	●	●	●	●	●
135X17 MR FFG	FFG	3355-06-	L Ball							●			
135X17 MR FG	FG	3355-07-	M Ball			●							
135X17 MR GEBEDUR®	R	-	SET							●	●		
UY180GYS MR	R	6935-01-	SET					●		●	●		
UY180GYS MR FG	FG	3355-07-	M Ball							●			
1906 MR FFG	FFG	1906-06-	L Ball	●	●	●							
3386 MR	R	3386-01-	SET									●	
4510 MR FFG	FFG	4510-06-	L Ball					●		●			
5205 MR	R	5205-01-	SET							●			

Reports from practical users in the field confirm the progress achieved by the **MR needle**. The Groz-Beckert **MR needle** is distinguished by providing a longer service life particularly for automated sewing operations in wide-ranging different fields of application. **The results can be seen in a high standard of seam quality and optimum productivity.**

GROZ-BECKERT – THAT SUBTLE DIFFERENCE.

GROZ-BECKERT KG

PO Box 10 02 49

72423 Albstadt, Germany

Phone +49 7431 10-28 72

Fax +49 7431 10-32 00

s-vn@groz-beckert.com

www.groz-beckert.com

GEBEDUR® is a registered trade mark of the Groz-Beckert KG